WHAT IS CLAIMED IS:

 A network monitoring system for monitoring a communication state on a network in which action explanation information for explaining a single action is divided into a plurality of packets, the network monitoring system comprising:

a data acquisition section for acquiring the plurality of packets flown on the network;

a data analysis section for acquiring the action explanation information from the plurality of packets acquired by the data acquisition section; and

a display-information generation section for generating display information, which is used to display the single action on the network on a single screen on the basis of the action explanation information acquired by the data analysis section.

The network monitoring system according to claim
 wherein the action explanation information is defined in advance.

20

2.5

15

10

3. The network monitoring system according to claim 1, wherein the data analysis section identifies kinds of the packets acquired by the data acquisition section and acquires the action explanation information from the packets on the basis of the identified kinds of the packets.

- 4. The network monitoring system according to claim 1, wherein the action explanation information includes sending source computer information, destination computer information, and action information.
- The network monitoring system according to claim
 further comprising:

an analysis data storage section for storing the action

10 explanation information acquired by the data analysis section,

wherein:

the display-information generation section regenerates the display information used to play back and display the action explanation information stored by the analysis data storage section in response to a request of a user.

15

2.5

The network monitoring system according to claim
 wherein:

the action explanation information stored by the analysis

data storage section includes time information, which
corresponds to time at which the single action was performed;
and

the display-information generation section regenerates the display information used to play back and display the action explanation information stored by the analysis data storage

section in accordance with the time information, in response to a request of a user.

7. The network monitoring system according to claim 5 5, wherein the display-information generation section continuously plays back and displays the action explanation information stored by the analysis data storage section at the same time interval to an accuracy of 500 msec as the action was executed, in response to a request of a user.

10

15

25

- 8. The network monitoring system according to claim 1, wherein the display-information generation section extracts and generates the display information in accordance with display setting by a user.
- 9. A network monitoring method for monitoring a communication state on a network in which action explanation information for explaining a single action is divided into a plurality of packets, the method comprising:
- acquiring the plurality of packets flown on the network;
 acquiring the action explanation information from the
 plurality of acquired packets; and

generating display information, which is used to display the single action on the network on a single screen on the basis of the acquired action explanation information.

10. The network monitoring method according to claim 9, wherein the action explanation information is defined in advance.

5

10

15

25

- 11. The network monitoring method according to claim 9, wherein in the acquisition of the action explanation information, kinds of the packets acquired by the packet acquisition are identified and the action explanation information is acquired from the packets on the basis of the identified kinds of the packets.
- 12. The network monitoring method according to claim 9, wherein the action explanation information includes sending source computer information, destination computer information, and action information.
- 13. The network monitoring method according to claim9, further comprising:
- 20 storing the acquired action explanation information, wherein:

in the generation of the display information, the display information is regenerated, the regenerated display information used to play back and display the stored action explanation information in response to a request of a user.

14. The network monitoring method according to claim 13, wherein:

the stored action explanation information includes time information, which corresponds to time at which the single action was performed; and

in the generation of the display information, the display information is regenerated, the regenerated display information used to play back and display the stored action explanation information in accordance with the time information in response to a request of a user.

10

- 15. The network monitoring method according to claim 13, further comprising continuously playing back and displaying 15 the stored action explanation information at the same time interval to an accuracy of 500 msec as the action was executed in response to a request of a user.
- 16. The network monitoring method according to claim 9, wherein in the generation of the display information, the display information is extracted and generated in accordance with display setting by a user.
- 17. A network monitoring program for monitoring a 25 communication state on a network in which action explanation

information for explaining a single action is divided into a plurality of packets, the program making a computer perform a process comprising:

acquiring the plurality of packets flown on the network; acquiring the action explanation information from the plurality of acquired packets; and

generating display information, which is used to display the single action on the network on a single screen on the basis of the acquired action explanation information.

- 18. The network monitoring program according to claim 17, wherein the action explanation information is defined in advance.
- 15 19. The network monitoring program according to claim
 17, wherein in the acquisition of the action explanation
 information, kinds of the packets acquired by the packet
 acquisition are identified and the action explanation
 information is acquired from the packets on the basis of the
 20 identified kinds of the packets.
 - 20. The network monitoring program according to claim 17, wherein the action explanation information includes sending source computer information, destination computer information,
 - 25 and action information.

5

10

21. The network monitoring program according to claim 17, wherein:

the process further comprises storing the acquired action splanation information; and

in the generation of the display information, the display information is regenerated, the regenerated display information used to play back and display the stored action explanation information in response to a request of a user.

22. The network monitoring method according to claim 21, wherein:

10

1.5

20

the stored action explanation information includes time information, which corresponds to time at which the single action was performed; and

in the generation of the display information, the display information is regenerated, the regenerated display information used to play back and display the stored action explanation information in accordance with the time information in response to a request of a user.

23. The network monitoring program according to claim21, wherein the process further comprises:

continuously playing back and displaying the stored action explanation information at the same time interval to

an accuracy of 500 msec as the action was executed in response to a request of a user.

.

24. The network monitoring program according to claim 5 17, wherein in the generation of the display information, the display information is extracted and generated in accordance with display setting by a user.